PRO-C™

Simple programming and flexible station expansion make Pro-C the professional's choice for residential and light commercial systems.

KEY BENEFITS

- · Number of stations:
 - Modular Pro-C capacity from 4 to 16
 - Fixed PCC with 6- and 12-station options
- 3 independent irrigation programs (4 start times each) allow for customised scheduling
- 6-hour maximum station run time provides flexibility for differing application amounts
- 1 sensor input available for use with Solar Sync™ or any Clik sensors
- 1P/MV output for pump start relay and master valve activation
- Dedicated Solar Sync dial position provides logic for smart water savings
- Easy Retrieve[™] memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck™ provides simple diagnostics of faulty field wiring

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- · Approvals: UL, cUL, FCC, CE, RCM
- · Warranty period: 2 years



Plastic Indoor Height: 22.9 cm Width: 25.4 cm

Width: 25.4 cm Depth: 11.4 cm



Plastic Outdoor

Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm

PRO-C - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4			
1 Model	2 Transformer	3 Indoor/Outdoor	4 Options
PC-4 = 4-station base module controller	00 = 120 VAC	(blank) = Outdoor model (internal transformer)	(blank) = No option
PCC-6 = 6-station	01 = 230 VAC	i = Indoor model (plug-in transformer)	E = 230 VAC with European connections
PCC-12 = 12-station			A = 230 VAC with Australian connections (outdoor models have internal transformer with cord)

Examples

PC-400 = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet **PCC-601i-E** = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet

PCC-1200 = Fixed 12-station outdoor controller, internal 120 VAC transformer, and plastic cabinet

PC-SERIES STATION EXPANSION		
Modules	Description	
PCM-300	3-station plug-in module	
PCM-900	9-station plug-in module (maximum, one per controller)	

Compatible with:





Solar Sync Sensor Page 146

ROAM Remote Page 137 ROAM XL Remote Page 138

Soil-Clik Sensor Page 151



Smart WaterMark

Recognised as a responsible water-saving tool when used with a Solar Sync sensor $\,$